

## **APPLICATIONS:**

Indoor Outdoor Wood Natural Gas LP (Liquid Propane) Custom Finish Multi-Sided Availability DM 54 Chimney Eco-Steel Chimney Fire-Lite Application

## Make your ideal dream home a dream come true with Isokern's **Standard Series.**

As the first Isokern modular fireplace introduced in the United States, the modular construction of the Standard Series allows you to unleash your creative desires with a fireplace as unique as you are. Whether you choose wood burning, natural gas or liquid propane, the Standard Series sets the standard. In an outdoor application, this fireplace can be finished with any veneer including brick, stone, stucco, or tile.

## Specifications

**Please Note:** When using the Isokern brick ledge it is required that the firebox/smoke dome assembly include the placemaent of a 4" by 4" by 3/8" minimum steel angle across the firebox opening. This item can be sourced locally.

Framing & Weight							
Мос	lel	Minimum	n Framing	Weight			
36	(46	"w) x (65"h	n) x (26 3/4"d)	1205 lbs			
42	(52	"w) x (65"h	n) x (26 3/4"d)	1325 lbs			
46	(56	"w) x (65"h	n) x (26 3/4"d)	1450 lbs			

## **Front View** Side View ← H → – A — **Plan View** Damp ĸ B b D D S E -Ċ Ċ ∳ G Е F **↓** \_ M F

Š	Model	А	В	С	D	E	F	G
View	36	33"	63 1/4"	31 1/2"	27 1/4"	37 1/8″	43″	10 1/2"
ont	42	33"	63 1/4"	31 1/2"	33 1/4"	43 1/8″	49"	10 1/2"
Fre	46	43″	63 1/4"	31 1/2"	37 1/4"	47 1/8″	53"	10 1/2"

≥	Model	В	С	Н	I	J	К	L	М
Viev	36	63 1/4"	31 1/2"	25 1/4"	28 3/4"	34 1/2"	16″	8″	5″
Side <sup>1</sup>	42	63 1/4"	31 1/2"	25 1/4"	28 3/4″	34 1/2"	16″	8″	5″
Si	46	63 1/4"	31 1/2"	25 1/4"	28 3/4"	34 1/2"	16″	8″	5″

≥	Model	D	E	F	S	Т
Viev	36	27 1/4"	37 1/8″	43″	25 1/4"	20 1/4"
an	42	33 1/4"	43 1/8″	49″	25 1/4"	20 1/4"
ä	46	37 1/4"	47 1/8″	53″	25 1/4"	20 1/4"