





APPLICATIONS:

Indoor
Outdoor
Natural Gas
LP (Liquid Propane)
Unvented
Multi-Sided Availability
Combustible Floor Installation
Custom Finish

A gas fireplace blends seamlessly into your home's footprint, with Isokern's **Vent-Free Series**.

The Vent-Free series offers a variety of opening heights and is fully customizable to fit in with any design plan. With its large finished openings and see-thru availability, the Vent-Free Series is a perfect heating solution for any multi-family home, new home, remodeling project or outdoor concept.

Specifications


Please Note: Zero clearance to combustible material. Combustible framing at bottom, top, sides, and rear.

Combustible sheathing and trim must be kept a minimum of 12" from the top of opening, and a minimum of 8" to the sides.


Combustible mantels must be installed per installation manual. The projection into the room dictates minimum distance above opening.

| Framing & Weight | | | | | | |
|------------------|--------------------------------|----------|--|--|--|--|
| Mode | l Minimum Framing | Weight | | | | |
| 36 | 43"W x 37 1/2"H x 25 1/4"D | 715 lbs | | | | |
| 42 | 49"W x 37 1/2"H x 25 1/4"D | 820 lbs | | | | |
| 46 | 53"W x 37 1/2"H x 25 1/4"D | 880 lbs | | | | |
| 60 | 73 1/2"W x 40 1/2"H x 25 1/4"D | 1400 lbs | | | | |
| 72 | 86"W x 40 1/2"H x 25 1/4"D | 1700 lbs | | | | |


Front View



Side View



Plan View



| | Model | В | С | D | Е | F | G |
|-------|-------|---------|---------|---------|---------|---------|---------|
| Ŋ | 36 | 37 1/2" | 31 1/2" | 27 1/4" | 37 1/8" | 43" | 10 1/2" |
| View | 42 | 37 1/2" | 31 1/2" | 33 1/4" | 43 1/8" | 49" | 10 1/2" |
| Front | 46 | 37 1/2" | 31 1/2" | 37 1/4" | 47 1/8" | 53" | 10 1/2" |
| 댦 | 60 | 40 1/2" | 31 1/2" | 57 3/4" | 67 1/2" | 73 1/2" | 10 1/2" |
| | 72 | 40 1/2" | 31 1/2" | 70" | 80" | 85 7/8" | 10 1/2" |

| | Model | В | С | Н | J | М |
|------|-------|---------|---------|---------|---------|----|
| 3 | 36 | 37 1/2" | 31 1/2" | 25 1/4" | 34 1/2" | 5" |
| View | 42 | 37 1/2" | 31 1/2" | 25 1/4" | 34 1/2" | 5" |
| | 46 | 37 1/2" | 31 1/2" | 25 1/4" | 34 1/2" | 5" |
| Side | 60 | 40 1/2" | 31 1/2" | 25 1/4" | 34 1/2" | 5" |
| | 72 | 40 1/2" | 31 1/2" | 26 1/4" | 35 1/2" | 6" |

| Model | D | Е | F | S | Т |
|-------|----------------------|--|---|---|---|
| 36 | 27 1/4" | 37 1/8" | 43" | 25 1/4" | 20 1/4" |
| 42 | 33 1/4" | 43 1/8" | 49" | 25 1/4" | 20 1/4" |
| 46 | 37 1/4" | 47 1/8" | 53" | 25 1/4" | 20 1/4" |
| 60 | 57 3/4" | 67 1/2" | 73 1/2" | 25 1/4" | 20 1/4" |
| 72 | 70" | 80" | 85 7/8" | 26 1/4" | 20 1/4" |
| | 36 42 46 60 | 36 27 1/4" 42 33 1/4" 46 37 1/4" 60 57 3/4" | 36 27 1/4" 37 1/8" 42 33 1/4" 43 1/8" 46 37 1/4" 47 1/8" 60 57 3/4" 67 1/2" | 36 27 1/4" 37 1/8" 43" 42 33 1/4" 43 1/8" 49" 46 37 1/4" 47 1/8" 53" 60 57 3/4" 67 1/2" 73 1/2" | 36 27 1/4" 37 1/8" 43" 25 1/4" 42 33 1/4" 43 1/8" 49" 25 1/4" 46 37 1/4" 47 1/8" 53" 25 1/4" 60 57 3/4" 67 1/2" 73 1/2" 25 1/4" |